






SPECIFICATIONS

1. DVI
 - 1.1 Voltage: 40 VAC(RMS) Max.
 - 1.2 Current Rating: 1.5 Ampere per Contact
 - 1.3 Contact Resistance(UPPER): 30 Milliohms Max.
Contact Resistance(LOWER): 20 Milliohms Max.
 - 1.4 Insulation Resistance: 1000 Megohms Min.
 - 1.5 Dielectric Withstanding Voltage: 500V DC(RMS)
 - 1.6 Total Mating Force: 4.5 Kgf Max.
 - 1.7 Total Unmating Force: 1.0 Kgf Min.
 - 1.8 Operating Temperature: -55°C to +85°C

NOTES

1. MATERIAL:
 - Housing(UPPER):LCP Halogen-free, Color:Black.
 - Housing(LOWER):LCP Halogen-free, Color:Black.
 - Terminal:Copper Alloy.
 - Shell:SPCC.
 - Shield:Stainless Steel.
 - Boardlock:Copper Alloy.
 - Bracket:Zinc Alloy.
 - Screw:Copper Alloy.
2. FINISH:
 - Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Ared.
 - Shell:Nickel Plated.
 - Boardlock:Tin Plated.
 - Bracket:Nickel Plated.
 - Screw:Nickel Plated.
3. This Product is LEAD-FREE & HALOGEN-FREE Compliance Product.



RECOMMENDED P.C.B. LAYOUT

INSPECTION DIMENSION:(A)~(L)



Champyang International Ltd., Co

A0	RELEASED	Allen	2019-10-04
REV	DESCRIPTION.	APPD.	Date

FILE NO : ADV01 (Series)		TITLE 圖名		DVI-1 / DVI-I FEMALE RIGHT ANGLE		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.13 mm 0.00 mm ± 0.25 mm Ang: 0.0 = ±2°		PART NO. 料號		ADV01-F4F4C-1x2ME2H8		SCALE 比例	1:1
DRAWN BY 製圖		Ben	DATE 日期	2019-10-04	REV. 版本	A0	
CHECKED BY 審核		Allen	DATE 日期	2019-10-04			