




SPECIFICATIONS

- 1. D-SUB
- 1.1 Voltage: 250 VAC(RMS) Max.
- 1.2 Current Rating: 3 Ampere per Contact
- 1.3 Contact Resistance: 25 Milliohms Max.
- 1.4 Insulation Resistance: 5000 Megohms Min.
- 1.5 Dielectric Withstanding Voltage: 1000 VAC(RMS)
- 1.6 Total Mating Force: 6.0 Kgf Max.
- 1.7 Total Unmating Force: 1.2 Kgf Min.
- 1.8 Operating Temperature: -55°C to +85°C

NOTES

- 1. MATERIAL:
 - Housing:PBT, UL 94V-0, Color:Black.
 - Terminal:Copper Alloy.
 - Shell:SPCC.
 - Boardlock:Copper Alloy.
 - Bracket:Zinc Alloy.
- 2. FINISH:
 - Terminal:Gold Plated over Nickel at Contact Area.
 - Tin Plated over Nickel at Solder Ared.
 - Shell:Nickel Plated.
 - Boardlock:Tin Plated.
 - Bracket:Nickel Plated.
- 3. This Product is LEAD-FREE & RoHS Compliance Product.



INSPECTION DIMENSION:(A)~(M)

 Champyang International Ltd., Co

A0	RELEASED	Allen	2019-10-04
REV	DESCRIPTION.	APPD.	Date

FILE NO : ADA10 (Series)		TITLE 圖名		D-SUB 0.350*(8.89mm) FOOTPRINT 15 FEMALE HIGH DENSITY CONNECTOR /15 MALE HIGH DENSITY CONNECTOR, DUAL PORT		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.13 mm 0.00 mm ± 0.25 mm Ang: 0.0 = ±2°		PART NO. 料號		ADA10-6S6PB-1x2B112N0		SCALE 比例	1:1
DRAWN BY 製圖		Ben	DATE 日期	2019-10-04	REV. 版本	A0	
CHECKED BY 審核		Allen	DATE 日期	2019-10-04	