


RECOMMENDED PANEL CUT-OUT INSPECTION DIMENSION:(A)-(H)



Screw L=5.7 For Panel Thickness Between 1.2~2.0mm

### SPECIFICATIONS

1. D-SUB
  - 1.1 Voltage: 250 VAC(RMS) Max.
  - 1.2 Current Rating: 5 Ampere per Contact
  - 1.3 Contact Resistance: 10 Milliohms Max.
  - 1.4 Insulation Resistance: 5000 Megohms Min.
  - 1.5 Dielectric Withstanding Voltage: 1000V AC(RMS)
  - 1.6 Screwing torque : 3.0 Kgf.cm Max.
  - 1.7 Total Mating Force: 20.8 Kgf Max.
  - 1.8 Total Unmating Force: 3.5 Kgf Min.
  - 1.9 Operating Temperature: -55°C to +85°C
  - 1.10 Salt Spray: 48 Hours.
  - 1.11 Waterproof Rate: IP 67 Min.

### NOTES

1. MATERIAL:
  - Housing:PBT, UL 94V-0, Color:Black.
  - Terminal:Copper Alloy.
  - Shell:SPCC.
  - Boardlock:Copper Alloy.
  - Rivet:Copper Alloy.
  - Screw:Copper Alloy.
  - Waterproof Ring: Silica Gel.
  - Waterproof Glue: Epoxy.
2. FINISH:
  - Terminal:Full Gold Plated over Nickel Area.
  - Shell:Nickel Plated.
  - Boardlock:Tin Alloy.
  - Rivet:Nickel Plated.
  - Screw:Nickel Plated.
3. This Product is RoHS Compliance Product.



Champyang International Ltd., Co

A0	RELEASED	Allen	2019-10-07
REV	DESCRIPTION.	APPD.	Date

FILE NO : ADA12 ( Series)		TITLE 圖名		D-SUB WATERPROOF CONNECTORS, RIGHT ANGLE		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.13 mm 0.00 mm ± 0.25 mm		PART NO. 料號		ADA12-H3P-Lx22Q12N0		SCALE 比例	1:1
ANGULAR ±2°		DRAWN BY 製圖		Ben	DATE 日期	2019-10-07	REV. 版本
		CHECKED BY 審核		Allen	DATE 日期	2019-10-07	