


RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(G)

SPECIFICATIONS

- D-SUB
- 1.1 Voltage: 250 VAC(RMS) Max.
- 1.2 Current Rating: 3 Ampere per Contact
- 1.3 Contact Resistance: 25 Milliohms Max.
- 1.4 Insulation Resistance: 5000 Megohms Min.
- 1.5 Dielectric Withstanding Voltage: 1000V AC(RMS)
- 1.6 Total Mating Force: 6.0 Kgf Max.
- 1.7 Total Unmating Force: 1.2 Kgf Min.
- 1.8 Operating Temperature: -55°C to +85°C

NOTES

- MATERIAL:
Housing:PA9T, UL 94V-0, Color:Black.
Terminal:Copper Alloy.
Shell:SPCC.
Rivet:Copper Alloy.
- FINISH:
Terminal:Gold Plated over Nickel at Contact Area.
Tin Plated over Nickel at Solder Ared.
Shell:Nickel Plated.
Rivet:Nickel Plated.
- This Product is LEAD-FREE & RoHS Compliance Product.



Champyang International Ltd., Co

A0			
	RELEASED	Allen	2019-07-15
REV	DESCRIPTION.	APPD.	Date

FILE NO : ADA08 (Series)		TITLE 圖 名		D-SUB 15 FEMALE HIGH DENSITY STRAIGHT DIP MOUNT PLASTIC BOY 0.236"(6.00)		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.13 mm 0.00 mm ± 0.25 mm		PART NO. 料 號		ADA08-15F-1120313N1		SCALE 比例	1 : 1
		DRAWN BY 製 圖		Ben	DATE 日期	2019-07-15	REV. 版本
		CHECKED BY 審 核		Allen	DATE 日期	2019-07-15	