



P.C.B LAYOUT

NOTES:

1. MATERIAL:

REAR SHELL: SPCC t=0.3

HOUSING: THERMOPLASTIC, GLASS FIBER FILLED
UL 94V-0 RATED

CONTACT: PHOSPHOR BRONZE t=0.2mm

2. PLATING:

SHELL: 1= 120u" TIN OVER 50u" Cu

2= 80u" NICKEL OVER 50u" Cu

3= 120u" TIN/LEAD OVER 50u" Cu

CONTACT: UNDER PLATED 50u" NICKEL, OVER ALL
120u" TIN/LEAD IN SOLDERING AREA,
SELECTIVE GOLD PLATED CONTACT AREA.



Champyang International Ltd., Co

| | | | | | |
|----------------|--------------------|------------|---|-------|------------|
| FILE NO : | ADN01(Series) | TITLE | DIN 4PIN No Shielded SINGLE PORT DIP 90° | UNIT | mm |
| TOLERANCE(公差): | 0.000 mm ± 0.05 mm | PART NO. | ADN01-0104-F21-D-B | SCALE | 1:1 |
| | 0.00 mm ± 0.10 mm | DRAWN BY | Ben | DATE | 2019-11-14 |
| | 0.0 mm ± 0.20 mm | CHECKED BY | Allen | DATE | 2019-11-14 |
| REV | DESCRIPTION. | APPD. | Date | | |

| | | | | | |
|----|----------|-------|------------|--|--|
| A0 | RELEASED | Allen | 2019-11-14 | | |
| | | | | | |
| | | | | | |
| | | | | | |