

PC Board Layout
Component Side Shown

SPECIFICATION NOTES:

ELECTRICAL:

- VOLTAGE RATING: 125 VAC RMS
- CURRENT RATING: 1.5 AMP
- CONTACT RESISTANCE: 30mΩ MAX.
- INSULATION RESISTANCE: 500MΩMIN. AT 500V DC.
- DIELECTRIC STRENGTH: 1000 VAC 50Hz 1MINUTE

MECHANICAL:

- HOUSING/INSERT MATERIAL:
THERMOPLASTIC, PBT UL94V-0,COLOR BLACK
- CONTACT MATERIAL:PHOSPHOR BRONZE Ø0.46mm
- PLATING:GOLD PLATING OVER NICKEL, PLATED NICKEL 30-50U". SN 100-120U. GOLD PLATED ON CONTACT AREA FU"
- OPERATING LIFE:750 CYCLES MIN.

ENVIRONMENTAL:

- STORAGE:-40° C TO +85° C
- OPERATION: 0° C TO 75° C

Champyang International Ltd., Co

				FILE NO : ARJ01(Series)	TITLE 圖 名	RJ11 6P6C TOP ENTRY			UNIT 單位	mm inch
				TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	PART NO. 料 號	ARJ01-010606-X21			SCALE 比例	1:1
A0					DRAWN BY 製 圖	Kiddy	DATE 日期	2018-10-30	REV. 版本	A0
REV	DESCRIPTION.	APPD.	Date		CHECKED BY 審 核	Allen	DATE 日期	2018-10-30		

Page: 1 of 1