


MECHANICAL:



SPECIFICATION NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5 AMP
3. CONTACT RESISTANCE: 30mΩ MAX.
4. INSULATION RESISTANCE: 500MΩMIN. AT 500V DC.
5. DIELECTRIC STRENGTH: 1000 VAC 50Hz 1MINUTE

MECHANICAL:

1. HOUSING/INSERT MATERIAL:  
THERMOPLASTIC, PBT UL94V-0,COLOR BLACK
2. CONTACT MATERIAL:PHOSPHOR BRONZE  $\phi$ 0.46
3. PLATING:GOLD PLATING OVER NICKEL, PLATED NICKEL 30-50U". SN 100-120U. GOLD PLATED ON CONTENT AREA FU"
4. OPERATING LIFE:750 CYCLES MIN.

ENVIRONMENTAL:

1. STORAGE:-40° C TO +85° C
2. OPERATION: 0° C TO 75° C



Champyang International Ltd., Co

AO	RELEASED	Allen	2019-12-23
REV	DESCRIPTION.	APPD.	Date

FILE NO : ARJ01 ( Series)		TITLE 圖名		RJ45 Vertical,1X1 Port,Tht		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.75 mm 0.00 mm ± 0.15 mm .0 mm ±0.25 mm		PART NO. 料號		ARJ01-010808-F21-B		SCALE 比例	1:1
		DRAWN BY 製圖	Ben	DATE 日期	2019-12-23	REV. 版本	A0
		CHECKED BY 審核	Allen	DATE 日期	2019-12-23		