





MECHANICAL:



PC Board Layout
Component Side Shown

SPECIFICATION NOTES:

ELECTRICAL:

- VOLTAGE RATING: 125 VAC RMS
- CURRENT RATING: 1.5 AMP
- CONTACT RESISTANCE: 30mΩ MAX.
- INSULATION RESISTANCE: 500MΩMIN. AT 500V DC.
- DIELECTRIC STRENGTH: 1000 VAC 50Hz 1MINUTE

MECHANICAL:

- HOUSING/INSERT MATERIAL:
THERMOPLASTIC, PBT UL94V-0,COLOR GRAY
- CONTACT MATERIAL:PHOSPHOR BRONZE Ø0.46mm
- PLATING:GOLD PLATING OVER NICKEL, PLATED NICKEL 30-50U". SN 100-120U. GOLD PLATED ON CONTACT AREA FU"
- OPERATING LIFE:750 CYCLES MIN.

ENVIRONMENTAL:

- STORAGE:-40° C TO +85° C
- OPERATION: 0° C TO 75° C



Champyang International Ltd., Co

A0			
	RELEASED	Allen	
REV	DESCRIPTION.	APPD.	Date

FILE NO : ARJ01(Series)		TITLE 圖 名		RJ45 1X2 TOP ENTRY WITH METAL PEG		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm		PART NO. 料 號		ARJ01-020808-X20-A		SCALE 比例	1:1
		DRAWN BY 製 圖		Kiddy	DATE 日期	2018-11-03	REV. 版本
		CHECKED BY 審 核		Allen	DATE 日期	2018-11-03	