



RECOMMENDED P.C.B LAYOUT
INSPECTION DIMENSION:(A)~(H)

SPECIFICATIONS

1. SCSI
- 1.1 Current Rating: 1 Ampere per Contact
- 1.2 Contact Resistance: 35 Milliohms Max.
- 1.3 Insulation Resistance: 1000 Megohms Min.
- 1.4 Dielectric Withstanding Voltage: 500V AC(RMS)
- 1.5 Total Mating Force: 12.3 Kgf Max.
- 1.6 Total Unmating Force: 1.3 Kgf Min.
- 1.7 Operating Temperature: -55°C to +85°C

NOTES

1. MATERIAL:
 - Housing:PBT, UL 94V-0, Color:Black.
 - Terminal:Copper Alloy.
 - Shell:Zinc Alloy.
 - Boardlock:Copper Alloy.
 - Screw:Copper Alloy.
2. FINISH:
 - Terminal:Gold Plated over Nickel at Contact Area.
 - Tin Plated over Nickel at Solder Area.
 - Shell:Nickel Plated.
 - Boardlock:Tin Plated.
 - Screw:Nickel Plated.
3. This Product is LEAD-FREE & RoHS Compliance Product.



Champyang International Ltd., Co

FILE NO:	ASR01(Series)	TITLE	SCSI RIBBON 36S 磷銅G/F 鍍殼二爪鎖4.8 黑色PBT	UNIT	mm
TOLERANCE(公差):	0.000 mm ± 0.13 mm 0.00 mm ± 0.25 mm	PART NO.	ASR01-36F-2F22A12N0	SCALE	1:1
REV	DESCRIPTION.	APPD.	Date	REV.	A0
A0	RELEASED	Allen	2018-12-07	DATE	2018-12-07
				DATE	2018-12-07

DATE	2018-12-07	DATE	2018-12-07	DATE	2018-12-07
DATE	2018-12-07	DATE	2018-12-07	DATE	2018-12-07