






WITHOUT COVER



WITH COVER

- 1.Contact Resistance:40mOHM Max.;
- 2.Dielectric Withstanding Voltage:100V AC For 1 Minute;
- 3.Insulation Resistance:100M OHM Min.;
- 4.Mating And Unmating Force:  
Mating Force: 5~20N  
Unmating Force: 8~20N(0~1000cycle);  
6~20N(1001~10000cycle);
- 5.Durability:10000 Cycles;



Item	Title	Material	Dispose	Remark
1	Shell	Stainless Steel	Ni:30u" Min.	
2	GND Plate	Stainless Steel		
3	Mid Plate	Stainless Steel	Solder Tails: Matt Tin	
4	Top Contact	Copper Alloy	Mating Area: See P/N	
5	Bottom Contact	Copper Alloy	Solder Tails: Matt Tin	
6	Insulator	High Temperature Plastic	UL 94V-0	Black



Champyang International Ltd., Co

A0	RELEASED	Allen	2019-07-01
REV	DESCRIPTION.	APPD.	Date

FILE NO : AUC05 ( Series)		TITLE 圖名		USB 3.1 TYPE C FEMALE VERTICAL H13.0mm SMT TYPE		UNIT 單位	mm inch
TOLERANCE(公差): 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm		PART NO. 料號		AUC05-0124-141-S		SCALE 比例	1:1
		DRAWN BY 製圖		Ben	DATE 日期	2019-07-01	REV. 版本
		CHECKED BY 審核		Allen	DATE 日期	2019-07-01	A.0